

PAGE VALLEY FAIR – FAIR RULES FOR NON-INTERSTATE CLASSES

1. Weight classes 7,000lb., 9,000 lb. and 13,500 lb.
2. All tractors will be weighed at the Page Valley Fairgrounds on the day of the pull. All tractors will be re-weighed just before the pull
3. Maximum 2.4 intake allowed, open turbos allowed. A-pumps are allowed. Electric transfer pumps are allowed. Water injection is allowed.
4. Tractor must have a steel flywheel or have a safety blanket or 3/8-inch x 5 inch 360 degrees around the flywheel area of tractor.
5. If a tractor is original from the factory it can pull without such add-ons as a wheelie bar, roll bars, and seat belts.
6. No slots, plugs, or reducers allowed on or in turbocharger.
7. Intake hose must be easily removable so that charger can be checked.
8. Torque Converters and automatic shifts are permitted. No slipper clutches.
9. Contests open to two (2) wheel drive, rubber tired tractors. No 4-wheel drives, dual tires, chain, or studded tires. All power must be transmitted through the rear wheels.
10. The tire width is limited to a maximum of 24.5"
11. No mixing of fuels allowed. Tractor must use the fuel the factory engine was designed for.
12. A no-stripping regulation will be enforced only if parts removed render the tractor unsafe to drive. Specific items illegal to remove are front wheels, hood, grill assembly, rear fender. All sheet metal, hoods, fender, dash, grilles and fuel tanks must be in original location as from factory.
13. Any supplement to the drawbar such as hitching rings or plow couplers must conform to the 20" maximum height to the top of the device, parallel to the ground and a minimum of 18" from the center of the rear axle. Supplement drawbars must be a minimum of 1" thick and with at least a 3" hole. No weights or brackets may be within 8" side to side or 12" above center of hook.
14. Straight pipes will be allowed in place of vertical muffler if they extend 18" above the hood. Underneath exhaust systems must be factory system in original condition. No rain caps allowed.
15. Custom built weight frames are allowed behind front wheels. No weights shall exceed more than 24" in front of the foremost portion of the tractor.

No weights may extend past the rear tires and all weights must be secured. Any weight lost during pull is automatic disqualification.

16. Anyone under the age of 18 must have written permission from parent or guardian before he or she can pull.
17. If contestant desires to stop within 75 feet, he will have the option of a second pull. The first puller in each class has the right to pull in third place position if he is not pleased with his first pull, or can drop to last place to pull.
18. Tractor shall be subject to official Tech Inspection to pull.
19. Driver must be fully clothed. No shorts. Shoes required.
20. Any equipment lost while hooked to the sled is an automatic disqualification.
21. Tractor can only hook in two (2) classes.
22. All engines must be original size for tractor, OR factory updated engine.
23. Due to insurance regulations, tractor must be equipped with rollover equipment (rollover cage, etc.), driver must wear seatbelt.
24. Judges will have the right to stop a tractor if it is being operated in an unsafe manner before, during, or after the contest. No riders on tractors anytime.
25. No one will be allowed in the track area during the pull except: officials, drivers, and judges.
26. Only the driver will be allowed on the tractor after registration. Any passenger will cause disqualification. This will be strictly enforced because of insurance policy regulations.
27. Tractor must maintain stock appearance.
28. Skid bars or wheelie bars must be a minimum of 32" behind rear axle; no more than 10" off the ground. Pads of 5" x 5". Bars must support weight of tractor.
29. If you pull in the 6200 Open Tractor class you may not pull in the Farm Classes.